

SEABOARD ASPHALT PRODUCTS COMPANY

PRODUCT DATA DRIVEWAY SEALER

AE-36 HYBRID EMULSION DRIVEWAY SEALER

PRODUCT DESCRIPTION:	Hybrid Emulsion Driveway Sealer is formulated from base asphalt emulsion meeting Federal and State Specifications.	
BASIC USES:	Hybrid Emulsion Driveway Sealer is used as a protective coating on bituminous surfaces for fuel resistance and elements of the weather and traffic wear.	
LIMITATIONS:	DO NOT ALLOW material to freeze. DO NOT USE on concrete. Contains less than 50 g/L VOC's Does Not contain coal tar Contains 0.0% PAH content	
APPLICATION:	Hybrid Emulsion Driveway Sealer must be applied to a surface that is free from all foreign matter and residues. This material must remain under dry conditions until it is cured. This material can be applied by brush, squeegee, or spray equipment and should yield a coverage rate of 150-300 square feet per gallon.	
STORAGE:	Hybrid Driveway Sealer must be kept from freezing.	
COMPOSITION:	Asphalt	CAS 8052-42-4
	Polymer	Proprietary Blend
	Water	CAS 7732-18-5

This information is to assist customers in determining if this product is suitable for the proposed application, and to satisfy themselves as to the suitability of the contents. Nothing herein shall constitute a warranty, expressed or implied, including any warranty of merchantability or fitness, nor is protection from law or patent implied.

3601 FAIRFIELD ROAD
BALTIMORE, MARYLAND 21226
(410) 355-0330
(800) 536-0332
FACSIMILE (410) 355-5864