

# SEABOARD ASPHALT PRODUCTS COMPANY

## PRODUCT DATA **Industrial Maintenance** Coating

LN-11 EQUINOX TOP DRESSING SEALER

PRODUCT DESCRIPTION:	Seaboard Equinox Sealer is a film forming waterproof asphalt sealer formulated to meet Federal Specification TTC-494 Types I, II, and III.	
BASIC USES:	Seaboard Equinox Sealer is used as a tough and weather resistant pigmented coating on all types of steel, piping, industrial equipment chassis, radiators, burial vaults, concrete pre-cast, septic tanks, and concrete manholes, masonry and bituminous concrete surfaces. Equinox Sealer provides resistance against water, alkalis, acids ultraviolet light and staining.	
LIMITATIONS:	DO NOT HEAT container. Equinox cannot be used for paving. Contains less than 250 g/L VOC's.	
APPLICATION:	Seaboard Equinox Sealer may be brush, squeegee or spray applied onto a clean and dry surface. This material dries in one hour and cures in approximately five hours.	
STORAGE:	Seaboard Equinox Sealer should be kept in a warm area before usage during cold seasons, but this material can be used year round and the only protection would be from weathering on the container.	
COMPOSITION:	Asphalt	CAS 8052-42-4
	Solvent	CAS 64741-41-9
	Gilsonite	CAS 12002-43-6

This information is to assist customers in determining if this product is suitable for the proposed application, and to satisfy themselves as to the suitability of the contents. Nothing herein shall constitute a warranty, express or implied, including any warranty of merchantability or fitness, nor is protection from law or patent implied.

3601 FAIRFIELD ROAD  
BALTIMORE, MARYLAND 21226  
(410) 355-0330  
(800) 536-0332  
FACSIMILE (410) 355-5864

