



# LN-12 Seaboard Quick Drying Asphalt Paint

## Product Data Sheet



### Product Highlights

**Specification:**

TTC-494, Type I, II, and III

**Solids:**

> 70 %

**Application Rate:**

80-100 Square Feet per Gallon.

**Recoat Time:**

1 Hour Minimum

**Application Temperature Range:**

No Restrictions

SEABOARD ASPHALT  
PRODUCTS COMPANY  
3601 Fairfield Road  
Baltimore, MD 21226

1-800-536-0332  
1-410-355-0330

**Product Description:**

Seaboard Quick Drying Asphalt Paint is designed for federal specification TTC-494 Types I, II, and III. This material is a superior quick drying asphalt paint.

**Basic Uses:**

Seaboard Quick Drying Asphalt Paint is used as a tough and weather resistant coating on all types of steel, piping, industrial equipment chassis, radiators, burial vaults, concrete precast, etc.

**Storage and Limitations:**

- Do not heat container.
- Keep material in warm area before use and during cold weather.

**Application:**

Seaboard Quick Drying Asphalt Paint may be brushed, rolled, or sprayed onto a clean and dry surface. This material dries within one hour and cures within five hours. This product can be used year round.

**Coverage:**

80-100 Square Feet per Gallon.

**Composition and Safety:**

For complete safety information please review the Safety Data Sheet for this product.

Revision Date: 02/2017

This information is to assist customers in determining if this product is suitable for the proposed application, and to satisfy themselves as to suitability of the contents. Nothing herein shall constitute a warranty, expressed or implied, including any warranty of merchantability or fitness, nor is protection from law or patent implied.