



LN-22 Clippership Aluminum Fibre Coating

Product Data Sheet

Product Highlights

Specification:

ASTM D2824, Type III

Solids:

> 35 %

Application Rate:

75 Square Feet per Gallon.

Spray Equipment:

Airless or Piston Pump

VOC Content:

248 g/L, meeting applicable EPA, OTC, CARB, and SCAQMD Rules

SEABOARD ASPHALT
PRODUCTS COMPANY
3601 Fairfield Road
Baltimore, MD 21226

Phone: 1-800-536-0332
or 1-410-355-0330

Fax: 1-410-355-5864

Email:
sales@seaboardasphalt.com

Product Description:

LN-22 Clippership Aluminum Fibre Coating is designed for ASTM D2824, Type III specification. This is an asphalt cutback blended with aluminum paste, fibers, and other additives.

Basic Uses:

LN-22 Clippership Aluminum Fibre Coating is used as a protective coating. It offers a reflective aluminum surface for many applications.

Storage and Limitations:

- Do not heat container.
- Do not thin or exceed 900 RPM when mixing.
- Do not apply on surfaces with a coal tar coating, soft asphalt, or surfaces that hold ponded water.
- Do not back-brush or disturb product after the "leafing process" has begun or the surface may brown.
- Protect metal container from weathering due to exposure.

Application:

LN-22 Clippership Aluminum Fibre Coating should be applied to a surface thoroughly clean of all foreign matter. This material should be applied when the temperature is 50°F and rising for best results. The material should be stirred before use and may be applied with brush or spray equipment. This material can be used year round.

Coverage:

75 Square Feet per Gallon.

Composition and Safety:

For complete safety information please review the Safety Data Sheet for this product.

Revision Date: 01/2016

This information is to assist customers in determining if this product is suitable for the proposed application, and to satisfy themselves as to suitability of the contents. Nothing herein shall constitute a warranty, expressed or implied, including any warranty of merchantability or fitness, nor is protection from law or patent implied.