



# MP-49 Seaboard Brick Block Mastic

## Product Data Sheet

### Product Highlights

**Solids:**

> 65 %

**Application Rate:**

40-50 Square Feet per Gallon.

**Recoat Time:**

8 Hours Minimum

**Application Temperature Range:**

No Limit

SEABOARD ASPHALT  
PRODUCTS COMPANY  
3601 Fairfield Road  
Baltimore, MD 21226

**Phone:** 1-800-536-0332  
or 1-410-355-0330

**Fax:** 1-410-355-5864

**Email:**  
sales@seboardasphalt.com

**Product Description:**

Seaboard Brick Block Mastic is an asphalt cutback with 2% Neoprene added to perform as a brick block mastic binder.

**Basic Uses:**

Seaboard Brick Block Mastic is used for adhering brick or block in a paving application. This material also can be used in conjunction with a dampproofing membrane.

**Storage and Limitations:**

- Do not heat container.

**Application:**

Seaboard Brick Block Mastic must be applied to a surface free of foreign matter. This material should be applied by notched trowel and should yield a coverage area of 40-50 square feet per gallon. This product can be used year round.

**Coverage:**

40-50 Square Feet per Gallon.

**Composition and Safety:**

For complete safety information please review the Safety Data Sheet for this product.

Revision Date: 10/2016

This information is to assist customers in determining if this product is suitable for the proposed application, and to satisfy themselves as to suitability of the contents. Nothing herein shall constitute a warranty, expressed or implied, including any warranty of merchantability or fitness, nor is protection from law or patent implied.