

SEABOARD ASPHALT PRODUCTS COMPANY

PRODUCT DATA FLOOR MASTIC

MP-48 SEABOARD WOOD BLOCK MASTIC

- PRODUCT DESCRIPTION:** Seaboard Wood Block Mastic is an asphalt cutback with fibres and additives to perform as a floor block mastic binder and is 100% ASBESTOS-FREE.
- BASIC USES:** Seaboard Wood Block Mastic is used for adhering wood block flooring and wooden subflooring in gymnasiums to concrete or wood base. This material also can be used in conjunction with a dampproofing membrane.
- LIMITATIONS:** DO NOT HEAT container.
- APPLICATION:** Seaboard Wood Block Mastic must be applied to surface free of all foreign matter. This material should be applied with a notched trowel and should yield a coverage rate of 40-50 square feet per gallon or use wood block manufacturers recommendation.
- STORAGE:** Seaboard Wood Block Mastic can be used year round and the only protection would be from weathering on the container.
- COMPOSITION:**
- | | |
|-----------------|----------------|
| Asphalt | CAS 8052-42-4 |
| Mineral Spirits | CAS 64741-41-9 |
| Fibre | CAS 65996-61-4 |
| | CAS 9004-34-6 |
| Amine Salt | CAS 30113-45-2 |
| Clay | CAS 8031-18-3 |
- VOC CONTENT:** LESS THAN 350 g/L

This information is to assist customers in determining if this product is suitable for the proposed application, and to satisfy themselves as to the suitability of the contents. Nothing herein shall constitute a warranty, expressed or implied, including any warranty of merchantability or fitness, nor is protection from law or patent implied.

3601 FAIRFIELD ROAD
BALTIMORE, MARYLAND 21226
(410) 355-0330
(800) 536-0332
FACSIMILE (410) 355-5864