



# ACF-1 Rubberized Cold Pourable Crackfiller

## Product Data Sheet

### Product Highlights

**Solids:**

> 50%

**Coverage Rate:**

200 Linear Feet per Gallon

**Application Surfaces:**

Bituminous / Concrete Surfaces

**Application Temperature Range:**

Surface and Air - 45° F Minimum

SEABOARD ASPHALT  
PRODUCTS COMPANY  
3601 Fairfield Road  
Baltimore, MD 21226

**Phone:** 1-800-536-0332  
or 1-410-355-0330

**Fax:** 1-410-355-5864

**Email:**  
sales@seboardasphalt.com

**Product Description:**

ACF-1 Rubberized Cold Pourable Crackfiller is an asphalt emulsion fortified with latex and fillers.

**Basic Uses:**

ACF-1 Rubberized Cold Pourable Crackfiller is used as a cold pourable joint sealant in bituminous and concrete surfaces, which are up to 1" in width and ½" in depth.

**Storage and Limitations:**

- Do not allow ACF-1 Rubberized Crackfiller to freeze.

**Application:**

ACF-1 Rubberized Cold Pourable Crackfiller must be mixed well before use. Make sure, prior to application, that cracks are free from all foreign matter and debris. The material shall remain dry until it is fully cured. The material can be poured directly from the container into the crack being filled.

**Coverage:**

200 Linear Feet per Gallon for cracks ½" in width and ½" in depth.

**Composition and Safety:**

For complete safety information please review the Safety Data Sheet for this product.

Revision Date: 09/2016

This information is to assist customers in determining if this product is suitable for the proposed application, and to satisfy themselves as to suitability of the contents. Nothing herein shall constitute a warranty, expressed or implied, including any warranty of merchantability or fitness, nor is protection from law or patent implied.