

SEABOARD ASPHALT PRODUCTS COMPANY

PRODUCT DATA ROOF & DRIVEWAY PATCH

DP-1 TROWELABLE GRADE CRACKFILLER

PRODUCT DESCRIPTION: Seaboard Trowelable Grade Crackfiller is a ready-to-use mastic patch polymer modified asphalt emulsion and is 100% ASBESTOS-FREE.

BASIC USES: Seaboard Trowelable Grade Crackfiller is designed for heavy duty repairs and filling cracks in excess of 1/2" in width in asphaltic surfaces.

LIMITATIONS: DO NOT allow to freeze.

APPLICATION: Seaboard Trowelable Grade Crackfiller can be applied by trowel in a liberal fashion to fill the joint completely. This material should not be used when rain is eminent or the temperature is below 50° F.

STORAGE: Seaboard Trowelable Grade Crackfiller must be protected from freezing.

MATERIAL

SPECIFICATIONS:	Weight per Gallon @ 77° F, ASTM-D-1010	10.8-11.3
	Nonvolatile %, ASTM-D-2939	66.00-70.00
	Viscosity @ 77° F, ASTM-D-562	125 min.
	Penetration, ASTM-D-5	PASS
	Std. Spec. for Emulsified Asphalt	
	AASHTO Designation M140-70	meets spec.
	ASTM Designation D-977-73 & D-244	meets spec.
	Flammability	non-flammable

This information is to assist customers in determining if this product is suitable for the proposed application, and to satisfy themselves as to the suitability of the contents. Nothing herein shall constitute a warranty, express or implied, including any warranty of merchantability or fitness, nor is protection from any law or patent implied.

3601 FAIRFIELD ROAD
BALTIMORE, MARYLAND 21226
(410) 355-0330
(800) 536-0332
FACSIMILE (410) 355-5864