



LN-11 Equinox Asphalt Gilsonite Driveway Sealer

Product Data Sheet

Product Highlights

Solids:

> 65 %

Application Rate:

100 Square Feet per Gallon.

Dry Time:

2 to 4 Hours Minimum

Application Surfaces:

Bituminous Surfaces

Application Temperature Range:

No Limit

No Vehicle Traffic for 24 Hours

SEABOARD ASPHALT
PRODUCTS COMPANY
3601 Fairfield Road
Baltimore, MD 21226

Phone: 1-800-536-0332
or 1-410-355-0330

Fax: 1-410-355-5864

Email:
sales@seaboardasphalt.com

Product Description:

LN-11 Equinox Asphalt Gilsonite Driveway Sealer is a superior gilsonite driveway sealer that dries to a beautiful black glossy finish on the pavement surface.

Basic Uses:

LN-11 Equinox Asphalt Gilsonite Driveway Sealer is used as a rejuvenator and sealer on bituminous asphalt parking lots and driveways.

Storage and Limitations:

- Do not heat container.
- Do not apply on bituminous surfaces less than 90 days old, including driveways
- Do not apply on surfaces with a coal tar coating

Application:

LN-11 Equinox Asphalt Gilsonite Driveway Sealer should be applied to a thoroughly clean and dry bituminous surface after all cracks and holes have been filled with ACF-1 Crackfiller. The material may be applied by brush, squeegee, or spray equipment. This material can be used year round.

Coverage:

100 Square Feet per Gallon.

Composition and Safety:

For complete safety information please review the Safety Data Sheet for this product.

Revision Date: 07/2016

This information is to assist customers in determining if this product is suitable for the proposed application, and to satisfy themselves as to suitability of the contents. Nothing herein shall constitute a warranty, expressed or implied, including any warranty of merchantability or fitness, nor is protection from law or patent implied.