



RP-355e Coal Tar Emulsion Sealer

Product Data Sheet

Product Highlights

Solids:

50-55%

Application Rate:

Varies based on Modification.

Recoat Time:

8 Hours Minimum

Application Surfaces:

Bituminous Surfaces

Application Temperature Range:

Surface and Air - 50° F Minimum

SEABOARD ASPHALT
PRODUCTS COMPANY
3601 Fairfield Road
Baltimore, MD 21226

1-800-536-0332
1-410-355-0330

Product Description:

RP-355e Coal Tar Emulsion Sealer is designed for federal specification RP-355e. This material is a high solids coal tar emulsion with emulsifying agents and fillers.

Basic Uses:

RP-355e Coal Tar Emulsion Sealer is used to formulate a protective coating for all asphalt pavement surfaces. These surfaces include driveways, parking lots, and airport runways.

Storage and Limitations:

- Do not allow RP-355e Coal Tar Emulsion Sealer to freeze.
- Do not use RP-355e Coal Tar Emulsion Sealer on concrete.
- Do not use on bituminous surfaces less than four months old.

Application:

RP-355e Coal Tar Emulsion Sealer must be applied to a surface this is free from all foreign matter and debris. The material shall remain dry until it is fully cured. The material can be modified to incorporate aggregates, curing agents, or water to formulate the desired solids and aggregate ratios.

Coverage:

The coverage rate depends on the modification of the material.

Composition and Safety:

For complete safety information please review the Safety Data Sheet for this product.

Revision Date: 06/2015

This information is to assist customers in determining if this product is suitable for the proposed application, and to satisfy themselves as to suitability of the contents. Nothing herein shall constitute a warranty, expressed or implied, including any warranty of merchantability or fitness, nor is protection from law or patent implied.