



# TE-1 Rubberized Tar Emulsion Driveway Sealer

## Product Data Sheet

### Product Highlights

**Solids:**

> 35%

**Application Rate:**

80 Square Feet per Gallon.

**Recoat Time:**

2 Hours Minimum

**Application Surfaces:**

Bituminous Surfaces

**Application Temperature Range:**

Surface and Air - 50° F Minimum

**No Vehicle Traffic for 24 Hours**

SEABOARD ASPHALT  
PRODUCTS COMPANY  
3601 Fairfield Road  
Baltimore, MD 21226

**Phone:** 1-800-536-0332  
or 1-410-355-0330

**Fax:** 1-410-355-5864

**Email:**  
sales@seaboardasphalt.com

**Product Description:**

TE-1 Rubberized Tar Emulsion Driveway Sealer formulated from a base coal tar emulsion designed for federal specification RP-355e. This material is a coal tar emulsion with polymer.

**Basic Uses:**

TE-1 Rubberized Tar Emulsion Sealer is used as a protective coating on asphalt pavement surfaces from petroleum remnants, weather, and traffic wear.

**Storage and Limitations:**

- Do not allow TE-1 Rubberized Tar Emulsion Sealer to freeze.
- Do not use TE-1 Rubberized Tar Emulsion Sealer on concrete.
- Do not use on bituminous surfaces less than four months old.

**Application:**

TE-1 Rubberized Tar Emulsion Sealer must be applied to a surface this is free from all foreign matter and debris. The material shall remain dry until it is fully cured. The material can be applied by brush, squeegee, or spray equipment. The application surface should be slightly damp for best results.

**Coverage:**

80 Square Feet per Gallon.

**Composition and Safety:**

For complete safety information please review the Safety Data Sheet for this product.

Revision Date: 07/2016

This information is to assist customers in determining if this product is suitable for the proposed application, and to satisfy themselves as to suitability of the contents. Nothing herein shall constitute a warranty, expressed or implied, including any warranty of merchantability or fitness, nor is protection from law or patent implied.