



MP-33 Clippership Heavy Duty Industrial Asphalt Mastic

Product Data Sheet

Product Highlights

Solids:

> 50 %

Application Rate:

40 Square Feet per Gallon.

Recoat Time:

4 Hours Minimum

Application Surfaces:

Multiple Surfaces

Application Temperature Range:

No limit

SEABOARD ASPHALT
PRODUCTS COMPANY
3601 Fairfield Road
Baltimore, MD 21226

Phone: 1-800-536-0332
or 1-410-355-0330

Fax: 1-410-355-5864

Email:
sales@seaboardasphalt.com

Product Description:

Clippership Heavy Duty Industrial Asphalt Mastic is designed for ASTM A849 specifications and is 100% ASBESTOS-FREE. This material is a self-healing type asphalt cutback fortified with mineral stabilizers and fillers.

Basic Uses:

Clippership Heavy Duty Industrial Asphalt Mastic is a multi-purpose protective coating used as a moisture barrier on felt and metal roofs, siding, and masonry surfaces above and below grade.

Storage and Limitations:

- Do not heat container.

Application:

Clippership Heavy Duty Industrial Asphalt Mastic must be applied to a surface that is dry and clean of all foreign matter. This material should be kept in a warm area and stirred before use. This material can be applied by brush, trowel, or spray at a rate of 40 square feet per gallon.

Coverage:

40 Square Feet per Gallon.

Composition and Safety:

For complete safety information please review the Safety Data Sheet for this product.

Revision Date: 09/2016

This information is to assist customers in determining if this product is suitable for the proposed application, and to satisfy themselves as to suitability of the contents. Nothing herein shall constitute a warranty, expressed or implied, including any warranty of merchantability or fitness, nor is protection from law or patent implied.