

BOND-X GREEN

HIGH PERFORMANCE COLD MIX

Seaboard BOND-X GREEN High Performance Cold Patch is a high quality, pre-mixed, all weather, permanent asphalt “cold patch” compound. Combining a carefully selected aggregate with a special bitumen formula using a biodegradable, renewable, organic solution to replace petroleum derivatives normally found in conventional cold mix asphalt. **Seaboard BOND-X GREEN High Performance Cold Patch** is the right choice for all types of pavement repair jobs. **Seaboard BOND-X GREEN High Performance Cold Patch** repairs dangerous potholes, wide cracks, ruts, etc.; within minutes, regardless of the weather outside. Suitable for use on both concrete and asphalt pavements. **Seaboard BOND-X GREEN High Performance Cold Patch** is highly recommended for spot repairs to driveways and dry pavement with no loss of bonding ability. The most important benefit to remember is the fact the **Seaboard BOND-X GREEN High Performance Cold Patch** is the “Permanent Patch” and should remain in the repaired area indefinitely. Money will be saved in labor cost because workers will not be constantly repairing an area where a other types of “cold patch” asphalt mix was used. **Seaboard BOND-X GREEN High Performance Cold Patch** is easy to apply with most repairs taking only a few minutes to complete. As an added feature, **Seaboard BOND-X GREEN High Performance Cold Patch** can be open to traffic immediately after it has been used.

PREPARATION: Simply sweep out the area to be repaired with a bristled brush or broom. It is a good idea to remove any loose debris, dirt, ice, or standing water from the area to be repaired. This action will promote good adhesion and bonding.

APPLICATION: No heating or mixing is required. Simply shovel into the pothole, crack, or rut, straight from the container. If the fault is especially deep, i.e. over six inches, apply in two inch layers, compacting each layer in succession. Shovel enough material into the fault to slightly crown the “patch”. When completed compress the “patch” with the pneumatic tamper. Area can be opened to traffic immediately.

COVERAGE: Depth and width of pothole, crack, utility cut etc. will greatly influence the coverage rate achieved. As a rule however, forty pounds of Seaboard BOND-X GREEN High Performance Cold Patch will fill a two inch deep hole, four square feet in size..

COLOR: Black

DRYING TIME: Immediate, following compacting of material.

CLEAN UP: All tools should be cleaned immediately after use with a solvent base cleaner such as varsol, paint thinner or mineral spirits.

STORAGE: Always keep container tightly closed when not in use to prevent “hardening” over long periods of storage. Bulk stockpile does not require special storage for up to one year. Recommend to “turn” portion of pile prior to loading from stockpile and for extended storage life it is recommended to cover stockpile.

PACKAGING: Seaboard BOND-X GREEN High Performance Cold Patch is available in five gallon pails, 60# plastic bags, 50# plastic bags and bulk.

3601 FAIRFIELD ROAD
BALTIMORE, MARYLAND 21226
(410) 355-0330
(800) 536-0332
FACSIMILE (410) 355-5864