



EF-7 Clippership Non-Fibred Emulsion Coating

Product Data Sheet

Product Highlights

Specification:

ASTM D1227, Type III, Class I or II

Solids:

50%

Application Rate:

40 Square Feet per Gallon.

Application Temperature Range:

Surface and Air - 45° F and Rising

VOC Content:

0 g/L, meeting applicable EPA, OTC, CARB, and SCAQMD Rules

SEABOARD ASPHALT
PRODUCTS COMPANY
3601 Fairfield Road
Baltimore, MD 21226

Phone: 1-800-536-0332
or 1-410-355-0330

Fax: 1-410-355-5864

Email:
sales@seaboardasphalt.com

Product Description:

Clippership Non-Fibred Emulsion Coating is designed for ASTM D1227, Type III specification. This material is an asphalt emulsion with selected colloids to formulate a dampproofing coating.

Basic Uses:

Clippership Non-Fibred Emulsion Coating is used as a protective coating for a variety of applications on asphalt, metal, wood, and masonry surfaces.

Storage and Limitations:

- Do not allow material to freeze.
- Do not thin material.

Application:

Clippership Non-Fibred Emulsion Coating must be applied to a dry or damp surface free of foreign matter. This material should remain dry until it has cured. This material can be applied by brush, squeegee, or spray equipment. This product can also be applied to “green” concrete.

Coverage:

40 Square Feet per Gallon.

Composition and Safety:

For complete safety information please review the Safety Data Sheet for this product.

Revision Date: 09/2016

This information is to assist customers in determining if this product is suitable for the proposed application, and to satisfy themselves as to suitability of the contents. Nothing herein shall constitute a warranty, expressed or implied, including any warranty of merchantability or fitness, nor is protection from law or patent implied.