



# LN-13 Clippership Blind Nailing Cement

## Product Data Sheet

### Product Highlights

**Specification:**

ASTM D4479, Type II

**Solids:**

> 65 %

**Application Rate:**

40-50 Square Feet per Gallon.

**Recoat Time:**

8 Hours Minimum

**Application Temperature Range:**

No Limit

SEABOARD ASPHALT  
PRODUCTS COMPANY  
3601 Fairfield Road  
Baltimore, MD 21226

**Phone:** 1-800-536-0332  
or 1-410-355-0330

**Fax:** 1-410-355-5864

**Email:**  
sales@seaboardasphalt.com

**Product Description:**

Clippership Blind Nailing Cement is designed for ASTM D4479 Type II specification. This material is a cold process adhesive asphalt cutback fortified with fibres and fillers.

**Basic Uses:**

Clippership Blind Nailing Cement is a multi-purpose adhesive used with roll roofing, roofing fabrics, and a sealant to bond membranes.

**Storage and Limitations:**

- Do not heat container.
- Keep in a warm area.

**Application:**

Clippership Blind Nailing Cement must be applied to a surface free of foreign matter. This product should be stirred before use. This material can be applied by brush or trowel. This product can be used year round.

**Coverage:**

40-50 Square Feet per Gallon.

**Composition and Safety:**

For complete safety information please review the Safety Data Sheet for this product.

Revision Date: 10/2016

This information is to assist customers in determining if this product is suitable for the proposed application, and to satisfy themselves as to suitability of the contents. Nothing herein shall constitute a warranty, expressed or implied, including any warranty of merchantability or fitness, nor is protection from law or patent implied.