



LN-15 Clippership Asphalt Primer

Product Data Sheet

Product Highlights

Specification:

ASTM D41, SS-A-701, AASHTO M116

Solids:

> 68 %

Application Rate:

175 Square Feet per Gallon.

Dry Time:

4 to 8 Hours

VOC Content:

213 g/L, meeting applicable EPA, OTC, CARB, and SCAQMD Rules

SEABOARD ASPHALT
PRODUCTS COMPANY
3601 Fairfield Road
Baltimore, MD 21226

Phone: 1-800-536-0332
or 1-410-355-0330

Fax: 1-410-355-5864

Email:
sales@seaboardasphalt.com

Product Description:

Clippership Asphalt Primer is designed for ASTM D41, SS-A-701, and AASHTO M116. This material is a ductile dampproofing asphalt cutback primer.

Basic Uses:

Clippership Asphalt Primer is used in dampproofing, roofing, and waterproofing as a prime coat on most surfaces before subsequent application of finished asphalt products.

Storage and Limitations:

- Do not heat container.
- Do not apply if rain is eminent.
- Do not apply on asphalt or concrete surfaces less than one month old.
- Protect metal container from weathering due to exposure.

Application:

Clippership Asphalt Primer must be applied to a dry surface free of foreign matter. This material can be applied by brush or spray equipment. This product can be used year round.

Coverage:

175 Square Feet per Gallon.

Composition and Safety:

For complete safety information please review the Safety Data Sheet for this product.

Revision Date: 01/2016

This information is to assist customers in determining if this product is suitable for the proposed application, and to satisfy themselves as to suitability of the contents. Nothing herein shall constitute a warranty, expressed or implied, including any warranty of merchantability or fitness, nor is protection from law or patent implied.