



LN-2 Seaboard Non-Fibred Roof Coating

Product Data Sheet

Product Highlights

Specification:

ASTM D312, Type I

Solids:

> 68 %

Application Rate:

30 Square Feet per Gallon.

Dry Time:

4 to 8 Hours

VOC Content:

213 g/L, meeting applicable EPA, OTC, CARB, and SCAQMD Rules

SEABOARD ASPHALT
PRODUCTS COMPANY
3601 Fairfield Road
Baltimore, MD 21226

Phone: 1-800-536-0332
or 1-410-355-0330

Fax: 1-410-355-5864

Email:
sales@seaboardasphalt.com

Product Description:

Seaboard Non-Fibred Roof Coating is formulated with asphalt designed for ASTM D312 Type I specification. This material is an asphalt cutback for used as a highly ductile roof coating.

Basic Uses:

Seaboard Non-Fibred Roof Coating is an easy to apply product for metal and composite roofs in private and commercial applications. This product penetrates old and worn surfaces and restores new life, seals small cracks, and provides weathering durability.

Storage and Limitations:

- Do not heat container.
- Do not thin material.
- Place in a warm area 1-2 days prior to use.
- Protect metal container from weathering due to exposure.

Application:

Seaboard Non-Fibred Roof Coating must be applied to a roof surface free of foreign matter. This material may be applied by stiff broom, brush, squeegee, or spray equipment. A thick application will increase curing time. This product can be used year round.

Coverage:

30 Square Feet per Gallon.

Composition and Safety:

For complete safety information please review the Safety Data Sheet for this product.

Revision Date: 01/2016

This information is to assist customers in determining if this product is suitable for the proposed application, and to satisfy themselves as to suitability of the contents. Nothing herein shall constitute a warranty, expressed or implied, including any warranty of merchantability or fitness, nor is protection from law or patent implied.