



# LN-6 Clippership Fibred Roof Coating

## Product Data Sheet

### Product Highlights

**Specification:**

ASTM D4479, Type II

**Solids:**

> 70 %

**Application Rate:**

50 Square Feet per Gallon.

**Dry Time:**

4 to 8 Hours

**VOC Content:**

178 g/L, meeting applicable EPA, OTC, CARB, and SCAQMD Rules

SEABOARD ASPHALT  
PRODUCTS COMPANY  
3601 Fairfield Road  
Baltimore, MD 21226

**Phone:** 1-800-536-0332  
or 1-410-355-0330

**Fax:** 1-410-355-5864

**Email:**  
sales@seboardasphalt.com

**Product Description:**

Clippership Fibred Roof Coating is designed for ASTM D4479 Type II specification. This material is an asphalt cutback and is fortified with mineral fillers, fibers, and additives.

**Basic Uses:**

Clippership Fibred Roof Coating is used as a protective coating on commercial and residential cold applied roofing systems.

**Storage and Limitations:**

- Do not heat container.
- Protect metal container from weathering due to exposure.

**Application:**

Clippership Fibred Roof Coating must be applied to a surface free of foreign matter. This material can be applied with a roof brush, squeegee, or commercial spray equipment and must be stirred before use. This product can be used year round.

**Coverage:**

50 Square Feet per Gallon.

**Composition and Safety:**

For complete safety information please review the Safety Data Sheet for this product.

Revision Date: 01/2016

This information is to assist customers in determining if this product is suitable for the proposed application, and to satisfy themselves as to suitability of the contents. Nothing herein shall constitute a warranty, expressed or implied, including any warranty of merchantability or fitness, nor is protection from law or patent implied.