



Seaboard RC Tack Coat

Product Data Sheet

Product Highlights

Solids:

> 50 %

Coverage:

150 Square Feet Per Gallon

Maximum Storage Temperature:

180°F

Recommended Application**Temperature:**

125 - 180°F

SEABOARD ASPHALT
PRODUCTS COMPANY
3601 Fairfield Road
Baltimore, MD 21226

1-800-536-0332

1-410-355-0330

Product Description:

Seaboard RC Tack Coat is an asphalt cutback formulated to be a premium coating for penetration, priming, and binding bituminous surfaces. It is manufactured in accordance with ASTM D2028.

Basic Uses:

RC Tack is designed for use as a treatment to a bituminous surface before resurfacing.

Storage and Limitations:

- Do not heat container.
- Avoid weathering of the container.

Application:

Seaboard RC Tack should be applied to a surface free of all foreign matter. This material can be applied by brush, squeegee, or spray equipment.

Coverage:

150 Square Feet per Gallon.

Composition and Safety:

For complete safety information please review the Safety Data Sheet for this product.

Revision Date: 04/2016

This information is to assist customers in determining if this product is suitable for the proposed application, and to satisfy themselves as to suitability of the contents. Nothing herein shall constitute a warranty, expressed or implied, including any warranty of merchantability or fitness, nor is protection from law or patent implied.