



LN-4 Seaboard Non-Fibred Foundation Coating

Product Data Sheet

Product Highlights

Specification:

ASTM D449, Type I

Solids:

> 68 %

Application Rate:

40 Square Feet per Gallon.

Dry Time:

4 to 8 Hours

VOC Content:

213 g/L, meeting applicable EPA, OTC, CARB, and SCAQMD Rules

SEABOARD ASPHALT
PRODUCTS COMPANY
3601 Fairfield Road
Baltimore, MD 21226

Phone: 1-800-536-0332
or 1-410-355-0330

Fax: 1-410-355-5864

Email:
sales@seaboardasphalt.com

Product Description:

Seaboard Non-Fibred Foundation Coating is formulated with asphalt designed for ASTM D449 Type I specification. This material is an asphalt cutback for use in dampproofing and waterproofing. This material is impervious to water and remains pliable under normal conditions.

Basic Uses:

Seaboard Non-Fibred Foundation Coating is used when below grade water may cause deterioration or damage. This material can be used for private and commercial applications on metal tanks, metal and concrete pipes, foundations, or silos.

Storage and Limitations:

- Do not heat container.
- Protect metal container from weathering due to exposure.

Application:

Seaboard Non-Fibred Foundation Coating must be applied to a dry surface free of foreign matter. This material penetrates and seals without priming and should be applied from top to bottom. This product can be spray, brush, or roll applied. This product can be used year round.

Coverage:

40 Square Feet per Gallon, which can be achieved in one or two coats.

Composition and Safety:

For complete safety information please review the Safety Data Sheet for this product.

Revision Date: 01/2016

This information is to assist customers in determining if this product is suitable for the proposed application, and to satisfy themselves as to suitability of the contents. Nothing herein shall constitute a warranty, expressed or implied, including any warranty of merchantability or fitness, nor is protection from law or patent implied.