

SEABOARD ASPHALT PRODUCTS COMPANY

PRODUCT DATA ROOF COATING

EL-1 CLIPPERSHIP WHITE ELASTOMERIC ROOF COATING

PRODUCT DESCRIPTION:	Clippership White Elastomeric Roof Coating is an acrylic resin emulsion with additives to formulate a cold applied reflective coating.
BASIC USES:	Clippership White Elastomeric Roof Coating is used as a protective coating for a variety of roofing application where a white reflective surface is desired.
LIMITATIONS:	DO NOT ALLOW material to freeze.
APPLICATION:	Clippership White Elastomeric Roof Coating must be applied to a Surface that is free of all foreign matter. This material may be applied by roller or spray equipment and should yield a coverage rate of 1 1/2-2 gallons/100sq. ft. by brush roller or spray in two applications @ 3/4-1 gallon/sq. ft. DO NOT apply in high humidity or if rain or heavy dew is imminent. AVOID application where ponding water will occur. DO NOT apply below 50 °F.
STORAGE:	Clippership White Elastomeric Roof Coating must be kept from freezing.
COMPOSITION:	Acrylic Resin Titanium Dioxide Calcium Carbonate Silicates Water

This information is to assist customers in determining if this product is suitable for the proposed application , and to satisfy themselves as to the suitability of the contents. Nothing herein shall constitute a warranty, expressed or implied, including any warranty of merchantability or fitness, nor is protection from law or patent implied.

3601 FAIRFIELD ROAD
BALTIMORE, MARYLAND 21226
(410) 355-0330
(800) 536-0332

FACSIMILE (410) 355-5864