



# Seaboard Rubberized Crackfiller

## ACF-1

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 06/01/2015 Version: 1.0

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

Product form : Mixture  
Product name : Seaboard Rubberized Crackfiller  
Product code : ACF-1

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Crack Filler

##### 1.3. Details of the supplier of the safety data sheet

Seaboard Asphalt Products Co.  
3601 Fairfield Road  
Baltimore, MD 21226  
1-800-563-0332

##### 1.4. Emergency telephone number

Emergency number : CHEMTREC 1-800-424-9300

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

###### Classification (GHS-US)

Carc. 2 H351

##### 2.2. Label elements

###### GHS-US labeling

Hazard pictograms (GHS-US) :



GHS08

Signal word (GHS-US) : Warning  
Hazard statements (GHS-US) : H351 - Suspected of causing cancer  
Precautionary statements (GHS-US) : P201 - Obtain special instructions before use  
P202 - Do not handle until all safety precautions have been read and understood  
P280 - Wear protective equipment  
P308 + P313 - If exposed or concerned: Get medical advice/attention

##### 2.3. Other hazards

Other hazards not contributing to the classification : Vapors and gases from heated asphalt may contain hydrogen sulfide and may be irritating to the eyes and skin. Skin contact with asphalt may cause skin irritation and allergic reactions in some individuals. Hot material may cause burns.

##### 2.4. Unknown acute toxicity (GHS-US)

None of the ingredients in the mixture are of unknown toxicity

#### SECTION 3: Composition/information on ingredients

##### 3.1. Substance

Not applicable – product is a mixture

##### 3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
Asphalt	(CAS No) 8052-42-4	40 – 45*	Carc. 2, H351
Distillates, petroleum, solvent-refined heavy paraffinic	(CAS No) 64741-88-4	0 – 2*	Acute Tox. 4 (Inhalation:dust,mist), H332

\*The exact percentages have been withheld as a trade secret

#### SECTION 4: First aid measures

##### 4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the product label where possible). Suspected of causing cancer.  
First-aid measures after inhalation : Allow victim to breathe fresh air. Allow the victim to rest.

# Seaboard Rubberized Crackfiller

## ACF-1

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. For hot product, immediately immerse in or flush the affected area with large amounts of cold water to dissipate heat. Cover with clean cotton sheeting or gauze and seek medical attention. No attempt should be made to remove material from skin.
- First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

No additional information available

#### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

- Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.
- Unsuitable extinguishing media : Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

No additional information available

#### 5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Contain all water used for fire-fighting to the greatest extent possible.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including NIOSH approved positive-pressure breathing apparatus with full face mask and full protective equipment..

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

- Emergency procedures : Evacuate unnecessary personnel.

##### 6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.
- Emergency procedures : Ventilate area.

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

#### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

- Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

#### 7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep only in the original container in a cool, well ventilated place away from oxidizers, excessive heat, and open flame. Keep container closed when not in use. Do not freeze.
- Incompatible products : Strong bases. Strong acids.
- Incompatible materials : Sources of ignition. Direct sunlight.

#### 7.3. Specific end use(s)

No additional information available

# Seaboard Rubberized Crackfiller

## ACF-1

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### SECTION 8: Exposure controls/personal protection

##### 8.1. Control parameters

Asphalt (8052-42-4)		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	0.5 mg/m <sup>3</sup> Inhalable fraction
Hydrogen Sulfide (7783-06-4) may be released from this product		
USA ACGIH	ACGIH TWA (ppm)	1 ppm
USA ACGIH	ACGIH STEL (ppm)	5 ppm
USA OSHA	OSHA PEL (ppm) (Vacated limits)	10 ppm
USA OSHA	OSHA STEL (ppm) (Vacated limits)	15 ppm
USA OSHA	OSHA Ceiling (ppm)	20 ppm

##### 8.2. Exposure controls

Appropriate engineering controls	: Ensure that proper ventilation is provided to maintain exposures below regulated limits.
Personal protective equipment	: Avoid all unnecessary exposure. At a minimum wear long sleeved cotton shirt buttoned at the collar and full length cotton pants. Synthetic fibers can melt and adhere to the skin when heated. Do not fold back or roll up cuffs.
Hand protection	: Wear protective gloves that protect against thermal burns when handling hot material.
Eye protection	: Chemical goggles or safety glasses.
Respiratory protection	: Not typically required. In cases where exposures exceed occupational control limits, a NIOSH approved respirator is recommended.
Other information	: Do not eat, drink or smoke during use. Wash hands and other exposed areas after use.

#### SECTION 9: Physical and chemical properties

##### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: Black
Odor	: Organic
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 343.33 °C
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: No data available
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Solubility	: No data available
Log Pow	: No data available
Log Kow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available

# Seaboard Rubberized Crackfiller

## ACF-1

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### 9.2. Other information

No additional information available

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No additional information available

#### 10.2. Chemical stability

Not established.

#### 10.3. Possibility of hazardous reactions

Not established.

#### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

#### 10.5. Incompatible materials

Strong acids. Strong bases.

#### 10.6. Hazardous decomposition products

Hydrogen sulfide and other toxic vapors may be given off when heated excessively. Carbon monoxide. Carbon dioxide.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Likely routes of exposure : Skin and eye contact

Acute toxicity : Not classified

Asphalt (8052-42-4)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg

Distillates, petroleum, solvent-refined heavy paraffinic (64741-88-4)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	2.18 mg/l/4h
ATE US (vapors)	2.180 mg/l/4h
ATE US (dust, mist)	2.180 mg/l/4h

Skin corrosion/irritation : Not classified  
Serious eye damage/irritation : Not classified  
Respiratory or skin sensitization : Not classified  
Germ cell mutagenicity : Not classified  
Carcinogenicity : Suspected of causing cancer.

Asphalt (8052-42-4)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicology Program (NTP) Status	5 - Twelfth Report - Items under consideration
In OSHA Hazard Communication Carcinogen list	Yes

Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : Not classified

Potential Adverse human health effects and symptoms : Vapors and gases from heated asphalt may contain hydrogen sulfide and may cause eye, skin and respiratory tract irritation, headache and nausea. Ingestion or contact of hot material may cause burns on eyes, skin or gastrointestinal system. Asphalt may cause skin irritation with reddening, itching, burning and/or swelling and may cause allergic skin reaction in some individuals.

# Seaboard Rubberized Crackfiller

## ACF-1

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### SECTION 12: Ecological information

##### 12.1. Toxicity

###### Distillates, petroleum, solvent-refined heavy paraffinic (64741-88-4)

LC50 fish 1 > 5000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)

EC50 Daphnia 1 > 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)

##### 12.2. Persistence and degradability

###### Seaboard Rubberized Crackfiller ACF-1

Persistence and degradability Not established.

###### Asphalt (8052-42-4)

Persistence and degradability Not established.

##### 12.3. Bioaccumulative potential

###### Seaboard Rubberized Crackfiller ACF-1

Bioaccumulative potential Not established.

###### Asphalt (8052-42-4)

BCF fish 1 (no bioaccumulation expected)

Log Pow > 6

Bioaccumulative potential Not established.

##### 12.4. Mobility in soil

No additional information available

##### 12.5. Other adverse effects

Other information : Avoid release to the environment.

#### SECTION 13: Disposal considerations

##### 13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local, state, and federal regulations.

Ecology - waste materials : Avoid release to the environment.

#### SECTION 14: Transport information

##### Department of Transportation (DOT)

In accordance with DOT

No additional information available

##### Additional information

##### ADR

No additional information available

##### Transport by sea

No additional information available

##### Air transport

No additional information available

#### SECTION 15: Regulatory information

##### 15.1. US Federal regulations

###### Seaboard Rubberized Crackfiller ACF-1

SARA Section 311/312 Hazard Classes Delayed (chronic) health hazard

###### Asphalt (8052-42-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

###### Distillates, petroleum, solvent-refined heavy paraffinic (64741-88-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

# Seaboard Rubberized Crackfiller

## ACF-1

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### 15.2. International regulations

##### CANADA

###### Asphalt (8052-42-4)

Listed on the Canadian DSL (Domestic Substances List)

###### Distillates, petroleum, solvent-refined heavy paraffinic (64741-88-4)

Listed on the Canadian DSL (Domestic Substances List)

##### EU-Regulations

###### Asphalt (8052-42-4)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

###### Distillates, petroleum, solvent-refined heavy paraffinic (64741-88-4)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

No additional information available

##### Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

No additional information available

##### National regulations

###### Asphalt (8052-42-4)

Listed on the AICS (Australian Inventory of Chemical Substances)  
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory  
Listed on the Korean ECL (Existing Chemicals List)  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

###### Distillates, petroleum, solvent-refined heavy paraffinic (64741-88-4)

Listed on the AICS (Australian Inventory of Chemical Substances)  
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory  
Listed on the Korean ECL (Existing Chemicals List)  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

#### 15.3. US State regulations

##### California - Proposition 65

WARNING: This product contains chemicals known to the State of California to cause cancer.

#### SECTION 16: Other information

Other information : None.

Full text of H-phrases:

Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Carc. 2	Carcinogenicity Category 2
H332	Harmful if inhaled
H351	Suspected of causing cancer

SDS US (GHS HazCom 2012)

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*