



# Clippership Rubberized Tar Emulsion Filler and Sealer

## TE-2

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 06/01/2015 Version: 1.0

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product form : Mixture  
Product name : Clippership Rubberized Tar Emulsion Filler and Sealer  
Product code : TE-2

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Filler and Sealer

### 1.3. Details of the supplier of the safety data sheet

Seaboard Asphalt Products Co.  
3601 Fairfield Road  
Baltimore, MD 21226  
1-800-563-0332

### 1.4. Emergency telephone number

Emergency number : CHEMTREC 1-800-424-9300

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification (GHS-US)

Carc. 1A H350

### 2.2. Label elements

#### GHS-US labeling

Hazard pictograms (GHS-US) :



GHS08

Signal word (GHS-US) : Danger  
Hazard statements (GHS-US) : H350 - May cause cancer  
Precautionary statements (GHS-US) : P201 - Obtain special instructions before use  
P202 - Do not handle until all safety precautions have been read and understood  
P280 - Wear protective equipment  
P308 + P313 - If exposed or concerned: Get medical advice/attention

### 2.3. Other hazards

No additional information available

### 2.4. Unknown acute toxicity (GHS-US)

None of the ingredients in the mixture are of unknown toxicity

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
Quartz	(CAS No) 14808-60-7	20 – 25*	Acute Tox. 4 (Oral), H302 Carc. 1A, H350
Tar, coal, low-temperature	(CAS No) 65996-90-9	10 – 11*	Flam. Liq. 3, H226 Carc. 1A, H350

\*The exact percentages have been withheld as a trade secret

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the product label where possible).

# Clippership Rubberized Tar Emulsion Filler and Sealer

## TE-2

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

First-aid measures after inhalation	: Allow victim to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.
First-aid measures after eye contact	: Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation	: May cause cancer by inhalation.
------------------------------------	-----------------------------------

#### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

No additional information available

#### 5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Contain all water used for fire-fighting to the greatest extent possible.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

Emergency procedures	: Evacuate unnecessary personnel.
----------------------	-----------------------------------

##### 6.1.2. For emergency responders

Protective equipment	: Equip cleanup crew with proper protection.
Emergency procedures	: Ventilate area.

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up	: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.
-------------------------	--

#### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.
-------------------------------	---

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Keep only in the original container in a cool, well ventilated place away from oxidizers, excessive heat, and open flame. Keep container closed when not in use. Do not freeze.
Incompatible products	: Strong bases. Strong acids.
Incompatible materials	: Sources of ignition. Direct sunlight.

#### 7.3. Specific end use(s)

No additional information available

# Clippership Rubberized Tar Emulsion Filler and Sealer TE-2

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

Quartz (14808-60-7)		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	0.025 mg/m <sup>3</sup> (respirable)
OSHA	OSHA PEL	$\frac{10 \text{ mg/m}^3}{(\% \text{SiO}_2 + 2)}$ (respirable)

#### 8.2. Exposure controls

Appropriate engineering controls	: Ensure that proper ventilation is provided to maintain exposures below regulated limits.
Personal protective equipment	: Avoid all unnecessary exposure.
Hand protection	: Wear protective gloves.
Eye protection	: Chemical goggles or safety glasses.
Respiratory protection	: Not typically required.
Other information	: Do not eat, drink or smoke during use.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: Black
Odor	: Mild
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 100 - 526 °C
Flash point	: > 200 °C
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: 17 mm Hg
Relative density	: 1.2
Relative vapor density at 20 °C	: > 1
Solubility	: Negligible in water
Log Pow	: No data available
Log Kow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available

#### 9.2. Other information

No additional information available

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No additional information available

#### 10.2. Chemical stability

Not established.

#### 10.3. Possibility of hazardous reactions

Not established.

# Clippership Rubberized Tar Emulsion Filler and Sealer TE-2

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

### 10.5. Incompatible materials

Strong acids. Strong bases.

### 10.6. Hazardous decomposition products

Carbon monoxide. Carbon dioxide.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Likely routes of exposure : Skin and eye contact; Inhalation

Acute toxicity : Not classified

#### Quartz (14808-60-7)

LD50 oral rat	500 mg/kg
ATE US (oral)	500.000 mg/kg body weight

Skin corrosion/irritation : Not classified  
Serious eye damage/irritation : Not classified  
Respiratory or skin sensitization : Not classified  
Germ cell mutagenicity : Not classified  
Carcinogenicity : May cause cancer.

#### Tar, coal, low-temperature (65996-90-9)

IARC group	1 - Carcinogenic to humans
In OSHA Hazard Communication Carcinogen list	Yes

#### Quartz (14808-60-7)

IARC group	1 - Carcinogenic to humans
National Toxicology Program (NTP) Status	2 - Known Human Carcinogens
In OSHA Hazard Communication Carcinogen list	Yes

Reproductive toxicity : Not classified  
Specific target organ toxicity (single exposure) : Not classified  
Specific target organ toxicity (repeated exposure) : Not classified  
Aspiration hazard : Not classified  
Potential Adverse human health effects and symptoms : No additional information available  
Symptoms/injuries after inhalation : May cause cancer by inhalation.

## SECTION 12: Ecological information

### 12.1. Toxicity

No additional information available

### 12.2. Persistence and degradability

#### Clippership Rubberized Tar Emulsion Filler and Sealer TE-2

Persistence and degradability	Not established.
-------------------------------	------------------

### 12.3. Bioaccumulative potential

#### Clippership Rubberized Tar Emulsion Filler and Sealer TE-2

Bioaccumulative potential	Not established.
---------------------------	------------------

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

Other information : Avoid release to the environment.

# Clippership Rubberized Tar Emulsion Filler and Sealer TE-2

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local, state, and federal regulations.  
Ecology - waste materials : Avoid release to the environment.

### SECTION 14: Transport information

#### Department of Transportation (DOT)

In accordance with DOT  
No additional information available

#### Additional information

#### ADR

No additional information available

#### Transport by sea

No additional information available

#### Air transport

No additional information available

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

<b>Clippership Rubberized Tar Emulsion Filler and Sealer TE-2</b>	
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard
<b>Tar, coal, low-temperature (65996-90-9)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Quartz (14808-60-7)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

#### 15.2. International regulations

##### CANADA

<b>Tar, coal, low-temperature (65996-90-9)</b>
Listed on the Canadian DSL (Domestic Substances List)
<b>Quartz (14808-60-7)</b>
Listed on the Canadian DSL (Domestic Substances List)

##### EU-Regulations

<b>Tar, coal, low-temperature (65996-90-9)</b>
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
<b>Quartz (14808-60-7)</b>
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

No additional information available

#### Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

No additional information available

#### National regulations

<b>Tar, coal, low-temperature (65996-90-9)</b>
Listed on IARC (International Agency for Research on Cancer)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)

# Clippership Rubberized Tar Emulsion Filler and Sealer TE-2

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Quartz (14808-60-7)

Listed on IARC (International Agency for Research on Cancer)  
Listed on the AICS (Australian Inventory of Chemical Substances)  
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory  
Listed on the Korean ECL (Existing Chemicals List)  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)  
Listed as carcinogen on NTP (National Toxicology Program)  
Listed on the Canadian IDL (Ingredient Disclosure List)

### 15.3. US State regulations

#### California - Proposition 65

WARNING: This product contains chemicals known to the State of California to cause cancer.

### SECTION 16: Other information

Other information : None.

Full text of H-phrases:

Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Carc. 1A	Carcinogenicity Category 1A
Flam. Liq. 3	Flammable liquids Category 3
H226	Flammable liquid and vapor
H302	Harmful if swallowed
H350	May cause cancer

SDS US (GHS HazCom 2012)

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*